

KSTAR SR series high density cabinet



Models

Server Cabinet

Dimension WxDxH (mm) 600x1200x2000, 42U

Communication Cabinet

Dimension WxDxH (mm) 800x1200x2000, 42U

Features

- The cabinet has 42 RU useful for installation of standard equipment of 19".
- Static load capacity of 2510 kilograms.
- It has leveling legs and wheels for transport and fixing.
- It has positioning and grounding hardware, pre-installed at the factory.
- It has front and rear mounting rails adjustable in depth.
- It has a robust fastening system between racks to join them together and thus form uniform rows with the floor.
- Standard black, other color can be customized.

Doors and side panels.

- The doors are locked.
- The side panels are half height, with a total of four per cabinet.
- The front and rear doors have High density hexagonal mesh, ventilation rate is 75%.
- The doors have an opening of 120°.

Meet Standards.

- ANSI/AIARS-310-D.
- DIN41497, PART, IEC60297-2, DIN41494, PART7, GB/T3047.2-92; compatible.
- with 19 inch international standard, metric standard, STSL standard.

Materials.

- SPCC high-quality cold-roll steel plate.
- thickness :the square hole is 2.0mm, others are 1.2mm.
- treatment of degreasing, pickling, phosphating, electrostatic paint.

Accessories.

- The cabinets have horizontal tray type organizers for the arrangement of the cables for the upper part of the cabinets.
- The cabinet has horizontal organizers with hinge and lid.
- *Optional vertical organizers with hinge and lid (only for Communication Cabinet model).
- electrostatic painting.

1

CONTACT

Tel: +86-755-21389008 Ext8508, E-mail: sales@kstar.com
www.kstar.com

KSTAR